我们做的不仅是生产，
而是印刷人的健康

PrintBar®
印吧

健康让生活更美好



PRINTING MATERIAL

上海琛洁印刷材料有限公司
Shanghai chenjie printing materials co.,LTD

地址：上海市闵行区江凯路199号
199 jiangkai road,minhang district, Shanghai, China
全国服务热线：400-7753-668
电话（总机）：021-61311286　传真：021-61311286
网址：www.cjyscl.com
邮编：201114

扫描关注公众号

上海琛洁印刷材料有限公司
Shanghai chenjie printing materials co.,LTD

Advantages 公司优势






历程悠久 LONG HISTORY

10多年制造历史，中国代理商40多家。

More than 10 years of manufacturing history, China agent 40 more



产品稳定 PRODUCT STABILITY

适应各种机器，兼容各地区水质，使用方便，对设备无伤害。

Hdapt to all kinds of machines, compatible with the water quality of various areas, easy to use, no harm to the equipment




市场趋势 MARKET TREND

降低成本，身体健康，顺应市场环保绿色印刷需求。

Reduce cost, keep healthy and meet the market demand for green printing


品牌保护 BRAND PROTECTION



多渠道宣传，代理商区域政策保护严格，严查市场仿冒伪劣产品。

Multi-channel publicity, agents of strict regional policy protection, strictly inspect the market for counterfeit and shoddy products

Qualification 公司资质



VOC



MSDS



SGS



商标证书



协会单位



诚信企业




绿色印品供应商

生产车间/质量检测 >>
PRODUCTION WORKSHOP / QUALITY INSPECTION






阳图PS版　POSITIVE PLATE >>

阳图PS版具有性能稳定，感度快，显影宽容度大，耐印率高等特点，2005年上市以来，一直受到国内外客户的青睐。

PrintBarpositive ps plate has a stable performance,quick sensitivity, developing large tolerance, resistance rate is high, since going public. in 2005 has been received with customers at home and abroad.



技术参数/SPECIFICATION

版材类型	Plate type	阳图型PS版
感光波长	Photosensitive wavelength	320-450nm
曝光时间	Sensitising energy	30秒，约20个脉冲
显影时间	Developing time	20-40秒
分辨率	Resolving power	2-98%
耐印率	Press run	5-20万（不烤版）
安全灯	Safety ligh	黄灯

优势/ADVANTAGES


- 稳定性好
- 宽容度大
- 感度高
- 适用于所有主流晒版机 显影机及显影液

- Stability is good
- Developing large tolerance
- High sensitivity
- Good adaptability, most of the plate maker developing machine and developer

阳图CTCP版　CTCP PLATE >>

阳图CTCP版版具有性能稳定，感度快，网点清晰，耐印率高等特点，能满足CTCP版制版机和用户的需要。

PrintBar positive ctcp version has a stable performance, quick sensitivity, points clear, the resistance rate is high, can satisfy the ctcp platemaker and user needs.



技术参数/SPECIFICATION

版材类型	Plate type	阳图CTCP版
感光波长	Photosensitive wavelength	410nm
感光能量	Sensitising energy	50-60mj/cm^2
显影时间	Developing time	20-30秒
分辨率	Resolving power	2-98%
耐印率	Press run	5-10万（不烤版）
安全灯	Safety ligh	黄灯

优势/ADVANTAGES


- 稳定性好
- 宽容度大
- 耐印率高
- 适用于所有主流制版机 显影机及显影液

- Stability is good
- Developing large tolerance
- High rate of resistance to print
- Good adaptability, most of the plate maker developing machine and developer

阳图热敏CTP版　CTP PLATE >>

阳图热敏CTP版具有性能稳定，感度快，网点清晰，耐印率高等持点。

PrintBar thermal CTP plate has stable performane ,quick sensitivity,points clear,resistance rate is high.



技术参数/SPECIFICATION

版材类型	Plate type	热敏CTP版
感光波长	Photosensitive wavelength	830nm
感光能量	Sensitising energy	110-130mj/cm^2
分辨率	Developing time	（200LPi）1-99%
耐印率	Resolving power	5-10万（不烤版） 10-20万（烤版）

优势/ADVANTAGES


- 稳定性好
- 宽容度大
- 耐印率高
- 可明室操作
- 适用于所有主流制版机 显影机及显影液

- Stability is good
- Developing large tolerance
- High rate of resistance to print
- Can Ming room operation
  Good adaptability, most of the plate maker developing machine and developer

双涂层热敏CTP版　CTP PLATE >>

双涂热敏CTP版，具有无需烤版，极快的感光度，完美的解析度，成像稳定，超高耐印力等特点，是新型创新性板材，是中高端印刷的首选板材。

Double layer thermal CTP plate have the advantages of unbaked,high sensitivity, perfect resolution, good stability and long run length, it is the revolutionary printing pate, also is the best choice of medium and high-end printing customer.



技术参数/SPECIFICATION

版材类型 Product type	双层涂布阳图热敏CTP版 Double layer thermal ctp plate
适用类型 Application type	免烤版超长UV油墨及普通油墨印刷 extremely long run without baking fo uv ink printing
版基厚度 Plate thickness	0.15mm,0.20mm,0.25mm,0.30mm
最大短边尺寸 Maximum coil width	1350mm
感光波长 Spectrum wave length	830nm
曝光能量 Exposure energy	110-130mj/Cm
显影温度 Developing temperature	22-28℃
显影时间 Developing time	25-35S
安全灯 Safe-light	可明室操作两小时 2 hours under white light
分辨率 Resolution	1-99% at 200lpl
耐印率 Run-length	无需烤版,普通油墨35-40万印,UV油墨15-20万印。注:耐印率随印刷条件和成像内容的不同而有所变化. Normal ink:3500,000-4000,000 impressions unbaked. uv ink: 150,000-200,000 impressions unbaked (actual run length may vary according to printing machine,ink,paper eonditions)
贮存条件 Storage conditions	温度:10-25℃,温度40%~60%,避光,防潮,密封保存,堆叠不超过1.5米 The recommended storage conditions are 10-25℃, with 40%%-60% humidity Keep away from sunlight and humidity. Pack height no more than 1.5 meters

优势/ADVANTAGES

- 感光速度快
- 显影宽容度大
- 网点还原性好
- 耐印力超强

- high sensitivity,
- large developing latitude,
- excellent dot reproduction,
- super long run length

CTP版/PS版显影粉　CTP PLATE/PS PLATE >>

阳图PS版、CTP 版显影粉适用于进口版和国产版的显影，具有显影能力强、性能稳定、冲洗出的版材网点清晰、分辨率高、影像鲜明、非影像部分洁白等特点。可用于机显和手显。

Plate developer powder is applicable to the import and domestic plates, Advantages: good developing, stable performance excellent dot reappearance high resolution be used for hand and machine developing



技术参数/SPECIFICATION

产品类型	Product type	PD型阳图PS版/CTP版显影粉
显影粉配制	The instructuond	19.6公斤水=1袋粉剂搅拌5-10分钟至完全溶解 1瓶膏体(预先用热水化开)=20升显影液 Add 19.6 kg wate—Add 1PCS powde—st 5-10 mnutes uit the mas—Add 1 PCS paste—ti 5-10 munutes t the ma=20L davelope
显影温度	Developing temperature	23±2℃（温度过高会使版材网点还原性变差，同时造成耐印力低：稳固过低则显影不透）
使用方法	Instructions for use	搅拌5-10分钟至完全溶解 Stir for 5－10 minutes until completely dissolved.
保存条件	Storage temperature	5℃-30℃