107-6 Sheet-fed Offset Printing Ink

1. Application

Model 107-6 printing ink is developed at the latest European technology system, it is made from polymeric ,high-soluble resin ,new paste pigment .This product is suitable for printing packaging,advertisement,label, high-quality brochures and decorating products on art paper, coated paper, offset paper, cardboard, etc, especially suitable for medium and high-speed printing.

107-6 型印刷油墨是根据最新的欧洲技术系统开发的，
由聚合物，高可溶性树脂，新型糊状颜料制成。本产品适用
用于印刷包装，广告，标签，高质量的小册子和装饰
艺术纸，铜版纸，胶版纸，硬纸板等产品，特别适用于
中高速打印

2. Features

- Rich in printing layer
- Environment protecting
- Clear and complete in printing dots.
- Anti-skinning performance Quick-drying performance, quick setting, quick turn.
- Good watcr/ink balance.

丰富的印刷层
环境保护
清除并完成打印点。
防结皮性能快干性能，快速设置，快速转动。
良好的水墨平衡。

Properties

型号/项目 ITEM/TYPE	粘性 TACK VALUE	流动值 FLUIDITY (mm	微粒 PARTCLESZE （um）	光泽度 GLOSS	固着 SETTING(Min)	纸张干燥 PAPER DRT TIME (hr)	结皮 SKINTIME (hr)
红 MAGENTA	9.5-10.5	37±1	12.5	70	5	<8-10	120
黄 YELLOW	9-10	38±1	12.5	80	5	<8-10	120
蓝 CYAN	9-10	36±1	12.5	70	5	<8-10	120
黑 BLACK	9.5-10.5	36±1	12.5	75	5	<8-10	120
super black	9.5-10.5	36±1	12.5	75	5	<8-10	120

1 .Tack value: Thevaluemeasuredbyink-o-meterunder32°C and 400prmin one minute.
2.Set time: Printing adapter, 157gartpaper,the volume of ink - coating can be up to.125cc.
3.Condition of test: Room temperature25°C,humidity65%-70%.

耐性值：(Resistance)

型号/项目 ITEM/TYPE	光 LIGHT	热 HEAT	酸 ACID	碱 ALKALINE	醇 ALCOHOL	皂 SOAP
红 MAGENTA	5-6	5	5	5	4	5
黄 YELLOW	4	5	5	4	4	4
蓝 CYAN	5-6	5	5	5	5	5
黑 BLACK	7-8	5	5	5	5	5

Lightfastness:1-8(weak-strong)

Other:1-5(weak-strong)

Packing :

1kg/tin

3years(from the production date);

Product again st light and water

1KG 罐装

三年(生产之日起)避光、防水储存